O4-04 DETERMINATION OF NO AND NO2 AIRCRAFT EMISSION INDICES AT AIRPORTS BY OPEN-PATH DOAS

<u>K. Schäfer¹</u>, G. Schürmann¹, S. Emeis¹, C. Jahn¹, H. Hoffmann¹ ¹Forschungszentrum Karlsruhe, Institut für Meteorologie und Klimaforschung (IMK-IFU), Kreuzeckbahnstr. 19, 82467 Garmisch-Partenkirchen, Germany Phone: +498821 183 242, Fax: +49 8821 73573, E-mail: klaus.schaefer@imk.fzk.de

Emission indices for NO_x and CO are listed for each engine in a data base of the International Civil Aviation Organisation (ICAO) for four different thrust levels (idle, approach, cruise and take-off). But real emissions of aircraft at airport are not well known. These emissions are to be determined for different operational scenarios.

A method to determine emission indices of aircrafts is used, where concentration measurements of CO_2 together with other pollutants within the aircraft exhaust plumes are needed. During intensive measurement campaigns, concentrations of CO_2 , NO, NO₂ and CO were measured. The measurement techniques were Differential Optical Absorption Spectroscopy (DOAS) for NO and NO₂ as well as Fourier-Transform-Infrared (FTIR) spectrometry for CO_2 and CO. The advantage of these methods is that no operations on the airport are influenced during measurement times. Knowing the emission index of CO_2 from total combustion of kerosene the emission indices of the other compounds can be determined with the concentration measurements. Together with detailed observations of taxiway movements real in use emissions become available.

Field studies were conducted on two airports (Zurich airport ZRH and Budapest international airport BUD). The two studies focused on the emission rate estimation of CO and NO_X . The results are presented here as well as a comparison with ICAO emission indices.



Fig. 1: An example of NO_x- measurements at the airport Zurich. The string (HBIJO) shows the time of an aircrafts passing the measurement path and leading to enhanced concentrations.