

could be used to discriminate and shield neutrons and muons. Moreover, an active veto surrounding every detector module is considered.

This work has been supported by funds of the DFG (Transregio

27: Neutrinos and Beyond), the Excellence Cluster Universe and the Maier-Leibnitz-Laboratorium (Garching).

T 104: Niederenergie-Neutrino-Physik & Suche nach dunkler Materie 5

Zeit: Freitag 14:00–16:05

Raum: A140

Gruppenbericht

T 104.1 Fr 14:00 A140

Recent Results from the BOREXINO Experiment — ●MICHAEL WURM — for the BOREXINO Collaboration. Technische Universität München, Physik Department, E15 Lehrstuhl für Astroteilchenphysik; James-Franck-Str., 85748 Garching

The BOREXINO experiment aims at the detection of low-energetic solar neutrinos. 300 tons of organic liquid scintillator serve as target for neutrino-electron recoils that can be detected down to a threshold of several 100 keV. The necessary ultra-low background conditions have been achieved by multilayer shielding, use of radiopure materials, and purification of the target liquid. Data acquisition started in May 2007.

In this contribution, the most recent analysis of Berillium-7 neutrino events in BOREXINO is presented [PRL101:091302, 2008]. The first real-time measurement of Boron-8 neutrinos down to a threshold of 2.8 MeV is discussed. The comparison of the results of both measurements with the predictions of the Standard Solar Model confirms the MSW-LMA oscillation scenario at 1.8 sigma level [arXiv:0808.2868].

This work is partially funded by the Maier-Leibnitz-Laboratorium (Munich) and by the Exzellenzcluster "Universe".

T 104.2 Fr 14:20 A140

11C Analysis and Muon Tracking in Borexino for solar pep and CNO neutrino spectroscopy — ●WERNER MANESCHG — Max-Planck-Institut für Kernphysik, Saupfercheckweg 1, D-69117 Heidelberg, Germany

Borexino is an experiment for low-energy neutrino spectroscopy at the Gran Sasso underground laboratories. Since May 2007 Borexino is taking data. The achieved radiopurity and the statistics collected up to now allow to study the smaller solar neutrino fluxes from the pep fusion process and the CNO cycle. The main background source is ^{11}C induced by the in-situ muon flux. In 95% of cases a neutron is released by the parent ^{12}C . The ^{11}C -candidates can be tagged on an event-by-event basis by looking at the following threefold coincidence: (1) the parent muon, (2) the 2.2MeV gamma-ray from neutron capture on proton and (3) the decay of ^{11}C . The method is discussed including the tagging of ^{11}C and the muon track reconstruction. The strategy for the analysis of pep and CNO neutrinos is presented.

T 104.3 Fr 14:35 A140

Tagging of Cosmogenic Radionuclides and Muon-induced Neutrons in the solar Neutrino Experiment BOREXINO — ●QUIRIN MEINDL FOR THE BOREXINO-COLLABORATION — Technische Universität München

The BOREXINO experiment is a 300t liquid-scintillator detector designed for the real-time detection of solar neutrinos in the sub-MeV energy range. Effort is currently directed to the determination of the solar neutrino fluxes from the pep fusion process, the three neutrino emissions of the CNO cycle as well as the low energy part of the ^8B branch. However, the detection of these neutrino branches is affected by radionuclides induced by the atmospheric muon flux at the site of the experiment. These muon-induced radionuclides form the so-called cosmogenic background. The production of cosmogenic radionuclides is accompanied by the coincidence of atmospheric muons and the neutrons they knock out from ^{12}C . This Three-Fold-Coincidence (TFC) of parent muon, knock-off neutron and generated radionuclide is the only known method to reject this cosmogenic background within the data. A high efficiency in the detection of these muons and their knock-off neutrons is therefore crucial for a successful measurement of the pep and CNO neutrino signal. The Talk will give an overview of the TFC technique and the current status of the BOREXINO detection capability of muon-induced neutrons.

This work is supported by funds of the Maier-Leibnitz-Laboratorium (Munich), and the excellence cluster "Universe".

T 104.4 Fr 14:50 A140

Entwicklung und Test von Ionenquellen für die Transportsektion des Neutrinomassensexperimentes KATRIN — ●MARCEL C.R. ZOLL — Universität Karlsruhe (TH), Institut für Experimentelle Kernphysik

Das Experiment KATRIN am Forschungszentrum Karlsruhe zur Ruhemassenbestimmung des Neutrinos aus dem Elektronenspektrum des Betazerfalls von Tritium ist ein komplexes System aus verschiedenen Sektionen: Quelle, Transportstrecke, Spektrometer und Detektor. Jedes Segment muss darauf untersucht werden, ob die gestellten Anforderungen erfüllt werden. Gerade beim Abschnitt der Transport- und Pumpstrecke ist es wichtig den Einfluss von störenden Tritiumionen zu kennen, wie sie auch später im Experiment auftreten werden. Hierzu wird in drei Phasen das Konzept einer Ionenquelle entwickelt und realisiert. Mit dieser Ionenquelle kann am Bauteil direkt dessen Verhalten auf verschiedene Ionen unter laufzeitähnlichen Bedingungen nachgestellt und gemessen werden. Es werden vorgestellt: Der Aufbau und die Funktionsweise von KATRIN, besonders der Transportstrecke; die erste Proof-of-concept und die fertiggestellte (FT-ICR-)Test Ionenquelle der nächsten Generation, sowie die Anforderungen an die noch zu entwickelnde WGTS-Simulator Ionenquelle. Gefördert durch die DFG unter dem SFB TR27

T 104.5 Fr 15:05 A140

Tests with the second Differential Pumping Section for KATRIN — ●STRAHINJA LUKIC for the KATRIN-Collaboration — Universität Karlsruhe, Institut für Experimentelle Kernphysik

The Karlsruhe TRITium Neutrino experiment (KATRIN) aims at determining electron-neutrino mass from the beta-decay of tritium with unprecedented sensitivity of 0.2 eV/c². KATRIN comprises a Windowless Gaseous Tritium Source (WGTS), an electron-transport section, two high resolution electrostatic spectrometers and an electron detector. Along the electron-transport section, tritium will be pumped out for reprocessing and reinsertion into the source. Two stages of differential pumping followed by a cryogenic pumping system must reduce the tritium gas flow by a total factor of 10¹⁴ in order to avoid distortion of the electron energy spectrum and contamination of the spectrometers. In particular, the second Differential Pumping Section (DPS2-F) is constructed to reduce the flow of 10⁻² mbar l/s at its input by at least a factor of 10⁵. Beside that, DPS2-F will host devices for monitoring the concentration of ions produced in the WGTS and for their removal. In this talk a series of experiments will be described that aim at testing gas-flow reduction capabilities of the pumping section, as well as the performance of systems for ion-concentration measurement and for ion removal.

Supported by DFG in the framework of the SFB TR27.

T 104.6 Fr 15:20 A140

Calibration setup for testing vacuum-capabilities of the DPS2-F for KATRIN — ●ALEKSANDRA GOTSOVA for the KATRIN-Collaboration — Universität Karlsruhe (TH), Institut für Experimentelle Kernphysik

The Karlsruhe Tritium Neutrino experiment (KATRIN) aims to determine the neutrino mass from the tritium β -decay with 0.2eV sensitivity. The KATRIN setup consists of a tritium source, a transport system with differential (DPS) and a cryogenic pumping sections, a pre- and main spectrometer and a detector. The determination of the neutrino mass relies on the precise investigation of the high energy end of the tritium β spectrum using a high energy resolution electrostatic spectrometer with adiabatic magnetic collimation. The main objectives for the STS are: providing a windowless gaseous tritium source for the β -decay suppressing the tritium flow to the spectrometer by 14 orders of magnitude; preventing penetration of low energy ions to the spectrometer. The main differential pumping system (DPS2-F) consists of 5 beam tube sections separated by pumping chambers pumped by TMPs. Its tritium flow reduction factor (TRF) is expected to be 10e5. Inside the DPS2-F β -electrons are guided by SC solenoids with B =

5.6T. To measure the gas amounts being transferred through the DPS and to verify the TRF between the inlet and outlet part of the DPS2-F an injection-collection system (ICS) was built up as a test experiment. This talk reports on the complete test and calibration procedures of the ICS. In part supported by BMBF project 05CK5VKA/5 and by DFG in SFB/TR27 TP A1.

T 104.7 Fr 15:35 A140

Erste Laser-Raman-Messungen mit Tritium für KATRIN — ●MAGNUS SCHLÖSSER für die KATRIN-Kollaboration — Universität Karlsruhe (TH), Institut für Experimentelle Kernphysik

Das Karlsruhe TRITium Neutrino-Experiment KATRIN untersucht das Elektronenspektrum des Tritium β -Zerfalls nahe dem kinematische Endpunkt von 18,6 keV. Mit einer fensterlosen molekularen gasförmigen Tritiumquelle hoher Luminosität und einem hochauflösenden elektrostatischen Filter mit einer Energieauflösung von $\Delta E = 0,93 eV$, wird KATRIN eine modellunabhängige Bestimmung der Neutrinomasse mit einer erwarteten Sensitivität von 0,2 eV (90% CL) ermöglichen.

Um diese Präzision zu erreichen, ist die präzise Kenntnis der Zusammensetzung des in die Quelle eingespeisten Gases erforderlich. Zur Bestimmung der Anteile der verschiedenen Wasserstoff-Isotopologe wird ein Laser-Raman-System verwendet, welches die Überwachung der Zusammensetzung während der KATRIN-Messphasen ermöglicht. In diesem Vortrag werden der Aufbau des Laser-Raman-Systems und erste Messungen an Mischungen der verschiedenen Wasserstoff-Isotopologe vorgestellt.

Gefördert vom BMBF unter Förderkennzeichen 05A08VK2 und von

der DFG im Sonderforschungsbereich Transregio 27 "Neutrinos and Beyond" TPA1.

T 104.8 Fr 15:50 A140

Magnetfeldmessungen am KATRIN Experiment — ●SUSANNE MERTENS — Universität Karlsruhe (TH), Institut für Experimentelle Kernphysik

Das Ziel des KATRIN (KARlsruhe TRITium Neutrino) Experiments ist es, die Masse des Elektronantineutrinos mit einer Sensitivität von 0,2 eV direkt zu messen. Das Experiment basiert auf dem MAC-E-Filter Prinzip (Magnetic Adiabatic Collimation followed by Electrostatic Filter).

Die magnetische Kollimation basiert auf dem Zusammenspiel von Magnetfeldern, deren Feldstärke räumlich sehr stark variiert. Das Verhältnis der stärksten zur schwächsten Feldstärke und der räumliche Feldgradient bestimmen die Transmissionseigenschaften des Experiments. Neben der magnetischen Kollimation dient das Magnetfeld zur Abschirmung gegen Sekundärelektronen. Um das zu gewährleisten werden hohe Ansprüche an die Symmetrie des Magnetfelds gestellt. Deshalb ist eine präzise Messung und Überwachung des Feldes entlang des gesamten Experimentaufbaus notwendig.

Aus diesen Gründen wurde ein Magnetfeldüberwachungssystem entworfen, das eine Bestimmung des Magnetfelds an den kritischen Stellen des Experiments bis auf 0,1% ermöglichen soll. In diesem Vortrag sollen die physikalischen Anforderungen an das Magnetfeld erläutert und das Konzept zur Messung und Überwachung desselben vorgestellt werden.

Gefördert durch das BMBF unter Förderkennzeichen 05A08VK2, DFG SFB TR 27 TP A1.

T 105: Experimentelle Techniken der Astroteilchenphysik 1

Zeit: Donnerstag 16:45–18:55

Raum: M105

Gruppenbericht

T 105.1 Do 16:45 M105

Status of acoustic activities for neutrino detection at the South Pole — ●DELIA TOSI for the IceCube-Collaboration — DESY Platanenallee 6 - 15738 Zeuthen

South Pole ice is predicted to be the best medium for acoustic neutrino detection, and consequently a suitable location for a multi-km³ hybrid array combining optical, radio and acoustic detectors. To verify the estimates and therefore the feasibility of such a detector, it is necessary to measure *in situ* acoustic properties such as acoustic noise floor, background transients rate and characteristics, sound speed and attenuation length, as a function of depth and in the frequency range interesting for neutrino detection (1-100 kHz).

To accomplish these measurements, an array of acoustic transmitters and sensors, the South Pole Acoustic Test Setup (SPATS) has been deployed in the Antarctic ice in 2007. In addition, a retrievable transmitter ("pinger"), was operated in 6 water-filled IceCube holes, before the deployment of the optical string.

Since installation, the array has been taking data continuously. At present the sound speed profile has been measured versus depth for both pressure and shear waves. The features of the transient signals and noise floor have been determined; additional laboratory studies are underway to reduce uncertainties in the calibration. Inter-string runs using frozen-in transmitter as well as other pinger runs foreseen in the austral summer 2008-09 on longer baselines will improve the constraints on the attenuation length. The status and the updated results from the setup will be presented.

Gruppenbericht

T 105.2 Do 17:05 M105

Status des AMADEUS Projekts: Akustische Teilchendetektion im Mittelmeer — ●MAX NEFF für die ANTARES-KM3NeT-Erlangen-Kollaboration — ECAP, Universität Erlangen-Nürnberg, Physikalisches Institut I, Erwin-Rommel-Straße 1, 91058 Erlangen

In das Wasser-Cherenkov-Neutrinoteleskop ANTARES hat die Erlanger ANTARES-Gruppe im Rahmen ihrer Forschungs- und Entwicklungsarbeit zur akustischen Teilchendetektion das AMADEUS System, das aus 36 akustische Sensoren besteht, integriert. Akustische Teilchendetektion basiert auf dem thermo-akustischen Modell, das die Erzeugung akustischer Signale durch eine lokale Erwärmung des Mediums beschreibt. Diese resultiert aus der Energiedeposition einer neutrino-induzierten Teilchenkaskade. Das Potenzial der akustischen Detektion von ultrahochenergetischen Neutrinos liegt in der Reichweite von

Schallwellen in Wasser, die die von Licht in dem jeweils relevanten Frequenzbereich um etwa ein Größenordnung übersteigt. Dies ist ein wichtiger Aspekt bei der effizienten Instrumentierung großer Volumina, die zur Detektion von ultrahochenergetischen Neutrinos, deren Fluß sehr klein ist, notwendig sind. Die Ziele von AMADEUS sind Langzeitstudien des akustischen Untergrundes, sowie die Untersuchung von Filter- und Analysestrategien. Im Vortrag wird das System und der Status von AMADEUS vorgestellt mit besonderem Augenmerk auf Datennahme und On-line-Filter. Gefördert durch das BMBF (05 CN5WE1/7) und (05 A08WE1).

T 105.3 Do 17:25 M105

Eigenschaften der Sensoren des South Pole Acoustic Test Setups (SPATS) — ●BENJAMIN SEMBURG, KARL-HEINZ BECKER, KLAUS HELBING und TIMO KARG für die IceCube-Kollaboration — Bergische Universität Wuppertal, Fachbereich C, 42097 Wuppertal

Der akustische Nachweis ultrahochenergetischer Neutrinos ist neben der optischen Nachweismethode durch Cherenkov Licht und dem Nachweis über Radiostrahlung eine mögliche Technik auf dem Weg zu einem Neutrino Hybriddetektor am geographischen Südpol. Entscheidende akustische Eigenschaften, wie zum Beispiel die Abschwächlänge akustischer Signale im Eis, das tiefenabhängige Rauschen, die Schallgeschwindigkeit und die Quellen transienter Ereignisse werden zur Zeit mit dem South Pole Acoustic Test Setup (SPATS) am Südpol erforscht.

Dieser Vortrag präsentiert erste in-situ Ergebnisse und zeigt die winkelabhängige Sensitivität der verwendeten Sensoren. Sowohl die SPATS Sensoren als auch die zum Teil bei String D verwendeten HADES Sensoren (kunststoffummantelte Piezosensoren) wurden in einem 10 m³ Wasser fassenden Tank in Wuppertal auf ihre winkelabhängige Sensitivität hin untersucht. Außerdem wird die absolute Kalibration von Sensoren im Wassertank mit Hinblick auf die Rauschquellenverteilung im Südpoleis diskutiert. Des weiteren wurde die relative Sensitivitätsänderung mehrerer Sensoren unter verschiedenen Druckverhältnissen in einem Labor der Universität Uppsala (Schweden) untersucht. Diese Ergebnisse werden im Vortrag ebenfalls vorgestellt.

T 105.4 Do 17:40 M105

Kalibration von Hydrophonen zur Untersuchung akustischer Detektionsmethoden kosmischer Neutrinos — ●ALEXANDER ENZENHÖFER für die ANTARES-KM3NeT-Erlangen-Kollaboration — ECAP, Universität Erlangen-Nürnberg